

CSB									
TYPE	모델	SPEC							
		V	Ah (20hr)	L (±2.0 mm)	W (±2.0 mm)	h (±2.0 mm)	H (±2.0 mm)	Weight (kg)	Terminal types
EVH	EVH12150	12	15	151.0	98.0	97.5	101.8	4.60	F2 terminal -Faston Tab 250
	EVH12240	12	24	181.0	76.2	170.0	170.0	7.55	I1 terminal to accept M5 bolt
	EVH12390	12	39	195.6	130.0	154.8	178.3	11.50	B5 terminal to accept M6 nut & bolt
EVX	EVX1272	12	7.2	150.9	64.8	94.3	98.6	2.55	F1/F2-Faston Tab187/250
	EVX12120	12	12	151.0	98.0	94.1	100.3	3.83	F1/F2-Faston Tab187/250
	EVX12170	12	17	181.0	76.2	167.0	167.0	5.67	B1/B1B/B3 terminal to accept M5 bolt
	EVX12200	12	20	181.0	76.0	165.0	165.0	6.55	I1 terminal to accept M5 bolt
	EVX12260	12	26	166.0	175.0	125.0	125.0	8.65	I1 terminal to accept M5 bolt
	EVX12300	12	30	166.0	125.0	175.0	175.0	10.40	I1 terminal to accept M5 bolt
	EVX12340	12	34	195.6	130.0	154.8	178.3	10.77	B5 terminal to accept M6 nut & bolt
	EVX12400	12	40	197.0	165.0	170.4	170.4	13.20	I2 terminal to accept M6 bolt
	EVX12520	12	52	228.0	138.4	201.3	219.3	17.87	B4 terminal to accept M6 bolt
	EVX12650	12	65	349.4	166.0	174.9	174.9	22.20	I2 terminal to accept M6 bolt
	EVX12750	12	75	277.0	168.5	210.5	232.5	25.60	B6 terminal to accept M6 bolt