

CSB											
TYPE	모 델	SPEC									
		V	Ah (20hr)	Ah (10hr)	W (15min)	L (±2.5 mm)	W (±2.5 mm)	h (±2.5 mm)	H (±2.5 mm)	Weight (kg)	Terminal types
GP	GP645	6	4.5			70.0	48.0	102.1	107.5	0.84	F1/F2 terminal -Faston Tab 187/250
	GP672	6	7.2			151.0	34.0	94.5	100.7	1.22	F1/F2 terminal -Faston Tab 187/250
	GP6120	6	12			151.0	50.0	94.3	100.5	1.85	F1/F2 terminal -Faston Tab 187/250
	GP1245	12	4.5			92.8	69.9	102.3	107.7	1.66	F1/F2 terminal -Faston Tab 187/250
	GP1245 (12V16W)	12			16W	90.0	70.0	101.8	106.1	1.34	F1/F2 terminal -Faston Tab 187/250
	GP1272	12	7.2			150.9	64.8	94.3	98.6	2.40	F1/F2 terminal -Faston Tab 187/250
	GP1272(12V25W)	12			24.5W	150.9	64.8	94.3	98.6	1.84	F1/F2 terminal -Faston Tab 187/250
	GP1272(12V28W)	12			28W	150.9	64.8	94.3	98.6	2.10	F1/F2 terminal -Faston Tab 187/250
	GP12120	12	12			151.0	98.0	94.1	100.3	3.67	F1/F2 terminal -Faston Tab 187/250
	GP12170	12	17			181.0	76.2	167.0	167.0	5.50	B1/B3/B1B terminal to accept M5 bolt
	GP12260	12	26			166.0	175.0	125.0	125.0	8.45	I1 thread lead alloy terminal to accept M5 bolt
	GP12340	12	34			195.6	130.0	154.8	178.3	10.48	B5 terminal to accept M6 bolt
	GP12400	12	40			197.0	165.0	170.4	170.4	12.92	I2 thread lead alloy terminal to accept M6 bolt
	GP12650	12	65			349.4	166.0	174.9	174.9	20.00	I2 terminal to accept M6 bolt
	GP121000	12	100			343.0	170.0	213.9	216.9	30.60	I2 terminal to accept M6 bolt
GPL	GPL1272	12	7.2			150.9	64.8	94.3	98.6	2.60	F1/F2 Faston Tab Terminal (187/250)
	GPL12120	12	12			151.0	98.0	94.1	100.3	4.10	F1/F2 Faston Tab Terminal (187/250)
	GPL12260	12	26			166.0	175.0	125.0	125.0	8.30	I1 thread lead alloy terminal to accept M5 bolt
	GPL12400	12	40			197.0	165.0	170.4	170.4	12.92	I2 thread lead alloy terminal to accept M6 bolt
	GPL12520	12	52			228.0	138.4	201.3	206.3	17.80	I2 thread lead alloy terminal to accept M6 bolt
	GPL12650	12	65			349.4	166.0	174.9	174.9	20.80	I2 thread lead alloy terminal to accept M6 bolt
	GPL12750	12	75			261.0	168.5	210.5	213.5	25.60	I2 thread lead alloy terminal to accept M6 bolt
	GPL12800	12	80			261.0	168.5	210.5	213.5	25.60	I2 thread lead alloy terminal to accept M6 bolt
	GPL12800G	12	80			277.0	168.5	210.5	213.5	25.60	I2 thread lead alloy terminal to accept M6 bolt
	GPL12880	12	88			308.7	169.0	210.6	213.6	29.70	I2 thread lead alloy terminal to accept M6 bolt
	GPL121000	12	100			343.0	170.0	213.9	216.9	33.50	I2 thread lead alloy terminal to accept M6 bolt
GH	GH12650	12		65		324.0	168.0	170.0	175.0	21.00	I2 thread lead alloy terminal to accept M6 bolt
	GH121000	12		100		329.0	175.0	215.0	221.0	30.50	I4 thread lead alloy terminal to accept M8 bolt
	GH121500	12		150		506.0	174.0	218.0	222.0	44.00	I4 thread lead alloy terminal to accept M8 bolt
	GH122000	12		200		520.0	239.0	219.0	223.0	58.00	I4 thread lead alloy terminal to accept M8 bolt