

CSB

TYPE	모델	SPEC									
		V	Ah (20hr)	W (15min)	W (5min)	L (±2.5 mm)	W (±2.0 mm)	h (±2.5 mm)	H (±2.5 mm)	Weight (kg)	Terminal types
XPL	XPL6700	12			6700W	343.0	170.0	273.2	275.7	47.90	I2 thread lead alloy terminal to accept M6 bolt
	XPL5700	12			5700W	343.0	170.0	213.9	216.9	36.90	I2 thread lead alloy terminal to accept M6 bolt
XHRL	XHRL12360W	12		360W		261.0	168.5	210.5	213.5	28.30	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12360WG	12		360W		277.0	168.5	210.5	213.5	28.30	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12410W	12		410W		308.7	169.0	210.6	213.6	32.60	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12410WG	12		410W		324.7	169.0	210.6	213.6	32.60	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12475W	12		475W		343.0	170.0	213.9	216.6	36.20	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12500W	12		500W		343.0	170.0	213.9	216.6	36.90	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12620W	12		620W		343.0	170.0	273.2	275.7	47.20	I2 thread lead alloy terminal to accept M6 bolt
	XHRL12650W	12		650W		343.0	170.0	273.2	275.7	47.90	I2 thread lead alloy terminal to accept M6 bolt
XTV	XTV1272	12	7.2			150.9	64.8	94.3	98.6	2.57	F2 terminal -Faston Tab 250
	XTV1285	12	8.5			150.9	64.8	94.3	98.6	2.62	F2 terminal -Faston Tab 250
	XTV12200	12	20			181.0	76.0	165.0	165.0	6.35	I1 thread lead alloy terminal to accept M5 bolt
	XTV12550	12	55			228.0	138.4	201.3	206.3	17.90	I2 thread lead alloy terminal to accept M6 bolt
	TV12800	12	80			261.0	168.5	210.5	213.5	25.50	I2 thread lead alloy terminal to accept M6 bolt
	XTV121000	12	100			308.7	169.0	210.6	213.6	30.20	I2 thread lead alloy terminal to accept M6 bolt
	XTV121100	12	110			343.0	170.0	213.9	216.9	34.20	I2 thread lead alloy terminal to accept M6 bolt